


Part Number	Thread Size	Length (Under Head) L	Spade			Projection	
			Width A (Ref.)	Thickness B	Length C (Ref.)	Diameter G	Height H
DW 2108	1/4-20	0.500	0.375	0.099	0.750	0.223	0.029
		0.470		0.089		0.213	0.025
DW 2712	5/16-18	0.750	0.438	0.130	0.875	0.286	0.029
		0.720		0.120		0.276	0.025



The DW weld screw is a long, narrow spade at right angles to the thread and a single button weld projection. The DW weld screw is particularly suitable for use in narrow channels, confined areas and corners. It can also be used in applications where threads must be offset from the surface. The DW weld screw is easy to locate and it produces a strong, sound weld.

Recommended hole in sheet is .015 above the major diameter.



Material: ..... C1010 High-Welding Quality, Low Carbon Steel      Finish: ..... Plain, Unless Specified

Threads: ..... Unified Standard Class 2A  
ASME B1.1-2003



## The Ohio Nut and Bolt Company

Sales Office: Buckeye Fasteners • "Your Factory Source"

5250 West 164th Street • Cleveland Ohio 44142

Ph: (800)-437-1689 • Ph: (216)-267-2240 • Fax: (216) 267-3228

[www.BuckeyeFasteners.com](http://www.BuckeyeFasteners.com)

A Division of Fastener Industries Inc. — An Employee Owned Company

© Copyright 2012 The Ohio Nut and Bolt Company

