


Part Number	Thread Size	Thickness Under Flange	Flange		Body Diameter	Projection	
			Dia.	Height		Dia.	Height
		L	A	H	D	P	F
RH 1104	#6-32	0.265	0.635	0.083	0.250	0.105	0.042
		0.245	0.605	0.073	0.244	0.095	0.038
RH 1404	#8-32	0.265	0.635	0.083	0.250	0.105	0.042
		0.245	0.605	0.073	0.244	0.095	0.038
RH 1505	#10-24	0.327	0.755	0.099	0.277	0.125	0.047
		0.307	0.725	0.089	0.271	0.115	0.043
RH 1605	#10-32	0.327	0.755	0.099	0.277	0.125	0.047
		0.307	0.725	0.089	0.271	0.115	0.043
RH 2138	1/4-20	0.390	0.835	0.130	0.375	0.135	0.052
		0.370	0.805	0.120	0.367	0.125	0.048
RH 2708	5/16-18	0.515	1.005	0.146	0.450	0.155	0.062
		0.495	0.970	0.136	0.442	0.145	0.058
RH 3308	3/8-16	0.515	1.005	0.146	0.500	0.155	0.062
		0.495	0.970	0.136	0.492	0.145	0.058



The RH weld nut is a self-locating, through-hole weld nut with a long body and three weld projections on the underside of the head. Its self-locating feature facilitates positive positioning of the nut in holes for welding operation. The location of the three spherical projections on the underside of the head permits the body of the nut to be attached through a hole in the component. This provides a flush surface to which mating parts can be attached.



The rugged extra-long body of the RH weld nut allows its use as a bearing surface or structural support.

Material:C1010 High-Welding Quality, Low Carbon Steel

Finish:Plain, Unless Specified

Threads:Unified Standard Class 2B ASME B1.1-2003



The Ohio Nut and Bolt Company

Sales Office: Buckeye Fasteners • "Your Factory Source"

5250 West 164th Street • Cleveland Ohio 44142

Ph: (800)-437-1689 • Ph: (216)-267-2240 • Fax: (216) 267-3228

www.BuckeyeFasteners.com

A Division of Fastener Industries Inc. — An Employee Owned Company

© Copyright 2012 The Ohio Nut and Bolt Company

