


Part Number	Thread Size	Width		Projection	
		A	Thick. B	Width	Height
				G	H
WS 1102	#6-32	0.438	0.116	0.083	0.027
		0.423	0.106	0.073	0.023
WS 1401	#8-32	0.438	0.195	0.083	0.027
		0.423	0.185	0.073	0.023
WS 1501	#10-24	0.438	0.195	0.083	0.027
		0.423	0.185	0.073	0.023
WS 1601	#10-32	0.438	0.195	0.083	0.027
		0.423	0.185	0.073	0.023
WS 2101	1/4-20	0.500	0.195	0.083	0.031
		0.485	0.185	0.073	0.027
WS 2102	1/4-20	0.562	0.226	0.099	0.037
		0.547	0.216	0.089	0.033
WS 2701	5/16-18	0.562	0.226	0.099	0.037
		0.547	0.216	0.089	0.033
WS 3301	3/8-16	0.625	0.257	0.114	0.037
		0.610	0.247	0.104	0.033



The WS weld nut is a square nut with four projections located to provide proper seating and sturdy positive welds. It also has deep threads for secure engagement and strength. The WS weld nut is also countersunk on both sides to guide the mating screw quickly into the threads. Rounded corners on the WS weld nut ease use in confined areas. The WS is easily fixtured for rapid welding by a locator pin in the electrode.

WS projection weld nuts provide strong, primary fastener foundations which can improve product reliability, speed production and help reduce fastening costs.



Material:C1010 High-Welding
Quality, Low Carbon Steel

Finish:Plain, Unless Specified

Threads:Unified Standard Class 2B
ASME B1.1-2003



The Ohio Nut and Bolt Company

Sales Office: Buckeye Fasteners • "Your Factory Source"

5250 West 164th Street • Cleveland Ohio 44142

Ph: (800)-437-1689 • Ph: (216)-267-2240 • Fax: (216) 267-3228

www.BuckeyeFasteners.com

A Division of Fastener Industries Inc. — An Employee Owned Company

© Copyright 2012 The Ohio Nut and Bolt Company

